

Explosion Proof Series CC03-2VF



Features

- Certified Explosion Proof Enclosure
- High Resolution 700 TVL Camera
- Advanced Vibration Damping Design
- 3.7 ~ 12mm Varifocal Auto-Iris Lens
- Epoxy Coated Die Cast Housing
- CSA / FM / ATEX / IEC Approvals
- IP66 Waterproof / Dustproof

Enclosure Certifications

FM Approvals

Explosion-proof for Class I, Division 1, Groups B, C and D;

Dust ignition-proof for Class II/III, Division 1, Groups E, F and G, hazardous (classified) locations, indoors and outdoors (Type 4X/IP66)

CSA

Explosion-proof for Class I, Division 1, Groups B, C and D;

Dust ignition-proof for Class II/III, Division 1, Groups E, F and G, hazardous (classified) locations, indoors and outdoors (Type 4X/IP66)

ATEX

II 2 G D, Ex d IIC, Ex tD A21, IP68, Ta = -40°C to +85°C

IEC EX

Ex d IIC, Ex A21 tD, IP68, Ta = -40°C to +85°C

Camera with Vibration Mount



Camera Specifications	CC03-2VF
Image Sensor	1/3" SONY ExView HAD II CCD
Resolution	700 TV Lines
Illumination	0.01 Lux / F1.2
S/N Ratio	More than 48 dB (AGC Off)
Lens	3.7 ~ 12.0mm Varifocal
Electronic Shutter	Auto (1/60sec ~ 1/100,000sec)
Sync System	Internal
Video Output	1 Vp-p / 75 ohms
Flickerless Mode	On
Gain Control	Hi / Low
White Balance	Auto
Backlight Compensation	Off (AES Off)
Gamma	r = 0.45
Power	12V DC
Power Consumption	120mA Max.
Operation Temp.	-40F ~ 104F (-40C ~ 50C)
Housing Specifications	
Construction	Epoxy Coated Die Cast Aluminum (Copper Free)
Color	Pantone 293 Blue
Ground Screws	Internal & External
Cover Set Screw	Tamper Resistant Cover Set Screws
O Ring	Buna N
Conduit Connections	2 x 1/2" NPT Standard Connections
External Mounting Holes	2 x 0.33in / 8.4mm
Dimensions (H x W)	4.86 x 5.65 inches / 12.4 x 14.4 cm
Weight	5 lbs (2.27 kg)