

OPTICOM

HD Wide Screen LCD CCTV Monitors

LCDI-27HDM, LCDI-32HDM, LCDI-42HDM



Features

- Full HD Wide Screen (16:9 Ratio)
- HDMI, DVI & Analog (BNC) Inputs
- 3D De-Interlace Technology
- Advanced Video Processor
- User Friendly Controls & OSD
- 3D Comb Filter Technology
- LED Backlight

Specifications	LCDI-27HDM	LCDI-32HDM	LCDI-42HDM
Operating System	NTSC / PAL Auto Switch		
LCD Panel	27" Wide Screen	32" Wide Screen	42" Wide Screen
Viewable Area	698 x 336 mm (H/V)	698 x 393 mm (H/V)	930 x 523 mm (H/V)
Aspect Ratio	16:9		
Maximum Resolution	1920 x 1080 (H/V)		
Display Colors	16.7M		
Brightness (nit)	450	400	450 (LED BL)
Contrast Ratio	5000:1	4000:1	
Response Time (Tr/Tf)	8 (G to G)		5.5 (G to G)
Viewing Angle (U/D/L/R)	89/89/89/89		
Input Video Signal	Composite Video, 1.0 Vp-p, 75 Ohms; Full HD (DVI/HDMI)		
Audio	2 x RCA In (L/R); 50~100m Vp-p; 1 x PC Audio In		
Impedance	75 Ohms Auto Termination		
Panel Frame	Aluminum		
Bracket	VESA Standard 100 / 200		
Video Connector	1 x BNC In; 2 x BNC Out; 1 x 4P Mini DIN In; 1 x 15 Pin D-Sub; 1 x DVI, 1 x HDMI, 1 x USB		
Operating Temperature	32°~122° F (0°~50° C)		
Power Supply	90~264 VAC, Global Switching Power Supply		
Power Consumption	22W	24W	26W
Dimensions (W x H x D)	25.6 x 15.6 x 2.4 inches 65.8 x 39.6 x 6.1 cm	29.7 x 17.8 x 3.4 inches 75.6 x 45.3 x 8.7 cm	40.1 x 24.1 x 4.8 inches 101.8 x 61.1 x 12.2 cm
Weight	15.4 lbs / 7.1 kg	30.9 lbs / 14 kg	61.7 lbs / 28 kg

Opticom Technologies Inc.
www.opticomtech.com
www.toughestvideocamera.com

USA Sales:
Canada:

Battle Creek, Michigan:
 Head Office (Vancouver):
 Quebec (Montreal):
 Maritimes (St. John):

800-578-1853
 855-569-3240
 888-222-3321
 888-224-3450