

LCDI-56T



## Features

- TFT LCD Panels
- BNC Video Inputs
- User Friendly Controls & OSD
- LED Backlight
- Battery Charger Included
- Lightweight & Portable

LCDI-4T



Specifications	LCDI-4T	LCDI-56T
Operating System	NTSC / PAL Auto Switch	
LCD Panel	4.0" TFT LCD	5.6" TFT LCD
Viewable Area	576 x 324 mm (H/V)	698 x 393 mm (H/V)
Maximum Resolution	480 x 234 (H/V)	640 x 480 (H/V)
Brightness (nit)	250	200
Contrast Ratio	150:1	500:1
Viewing Angle (U/D/L/R)	10/30/45/45	50/70/70/70
Video Input	1.0 Vp-p, 75 Ohms	
Video Connector	1 x BNC	2 x BNC
Audio	2 x RCA In	2 x AV Input (BNC)
Back Light	LED	
Case	Leather	Wood
Battery	Ni-MH Rechargeable Battery 6 x AA Size Charger Included	Rechargeable 12V, 1800mA Charger Included
Operating Temperature	32°~122° F (0°~50° C)	
Power Supply	12V DC	
Power Consumption	3W	3.6W
Dimensions (W x H x D)	6.0 x 4.2 x 1.5 inches 15.2 x 10.6 x 3.9 cm	9.6 x 6.7 x 2.9 inches 24.3 x 17.1 x 7.3 cm
Weight	0.63 lbs / 0.29 kg	4.7 lbs / 2.2 kg